



Dimensional data

MICHELIN van tyres

Rim Dia.	Size	Load Index & Speed Symbol	Range	Max Axle Load			Dimensional Details (mm)						Rim Width (inches)		Inner tube										
				Single Fit.	Twin Fit.	Pressure	SW	OD	RC	Design Dia	SLR	E mini	Min.	Measuring		Max.									
				kg	kg	psi																			
14"	185/80 R 14C	102/100R	AGILIS AGILIS X-ICE NORTH	1700 1547 1390	3200 2912 2617	65 58 51	193	664	1976	652	296	212	5.0	5.5	6.0	14 F 13									
	195/80 R 14C	106/104R	AGILIS	1900 1729 1554	3600 3276 2944	65 58 51	206	680	2024	668	303	225	5.0	5.5	6.0	14 F 13									
	165/75 R 14C	93/91R	AGILIS	1300 1087 940	2460 2058 1779	54 44 36	172	614	1830	604	277	190	4.0	4.5	5.0	14 D 13									
	165/70 R 14C	85R	AGILIS 41 REINF	1030	N/A	42	177	598	1782	588	271	196	4.5	5.0	5.0	14 D 13									
		89/87R	AGILIS AGILIS X-ICE NORTH	1160 970 839	2180 1824 1576	54 44 36																			
	175/65 R 14C	86T	AGILIS 41 REINF	1060	N/A	42	184	594	1170	584	269	204	5.0	5.0	5.5	T/L ONLY									
		90/88T	AGILIS 51 AGILIS 51 SNOW-ICE	1200 1004 868	2240 1874 1619	54 44 36																			
	15"	195/70 R 15C	98/96T	AGILIS 51	1500	2840	47	209			1985	655	300	231	5.0	5.5	6.0	15 F 13							
					1407	2664	44																		
			1216	2302	36																				
1800			3400	65																					
104/102R		AGILIS AGILIS ALPIN	1638	3094	58																				
			1472	2781	51																				
205/70 R 15C		106/104R	AGILIS AGILIS ALPIN	1900 1729 1554	3600 3276 2944	65 58 51	217	681	2027	669	306	240	5.5	6.0	6.5	15 F 13									
215/70 R 15C		109/107S 109/107R	AGILIS AGILIS ALPIN	2060 1875 1685	3900 3549 3190	65 58 51	230	695	2069	683	311	254	5.5	6.5	7.0	15/17H13									
225/70 R 15C		112/110S 112/110R	AGILIS AGILIS ALPIN	2240 2039 1832	4240 3859 3468	65 58 51	237	709	2112	697	317	262	6.0	6.5	7.0	15 J 13									
205/65 R 15C		102/100T	AGILIS 51 AGILIS 51 SNOW-ICE	1700 1422 1229	3200 2677 2314	54 44 36	217	657	1960	647	297	240	5.5	6.0	6.5	T/L ONLY									
215/65 R 15C		104/102T	AGILIS 51 AGILIS 51 SNOW-ICE	1800 1506 1301	3400 2844 2458	54 44 36	230	673	2003	661	303	254	6.0	6.5	7.0	T/L ONLY									
16"	175 R 16C	98/96Q	XC4S TAXI	1500 1255 1084	2840 2376 2053	54 44 36	186	698	2079	686	315	204	4.5	5.0	5.5	16 F 13									
	175/75 R 16C	101/99R	AGILIS	1650	3100	69	184	678	2024	668	308	204	4.5	5.0	5.5	16 F 13									
				1438	2702	58																			
				1292	2428	51																			
	185/75 R 16C	104/102R	AGILIS AGILIS ALPIN	1800 1569 1410	3400 2963 2663	69 58 51	191	696	2073	684	314	212	5.0	5.5	6.0	16 F 13									
	195/75 R 16C	107/105R	AGILIS AGILIS ALPIN	1950 1700 1527	3700 3225 2898	69 58 51	204	710	2115	698	320	225	5.0	5.5	6.0	16 F 13									

Rim Dia.	Size	Load Index & Speed Symbol	Range	Max Axle Load			Dimensional Details (mm)					Rim Width (inches)		Inner tube		
				Single Fit.	Twin Fit.	Pressure	SW	OD	RC	Design Dia	SLR	E mini	Min.		Measuring	Max.
				kg	kg	psi										
16" cont.	205/75 R 16C	110/108R	AGILIS AGILIS ALPIN	2120	4000	69	211	726	2163	714	326	240	5.5	6.0	6.5	15/17H13
				1848	3486	58										
				1660	3133	51										
		113/111R	AGILIS	2300	4360	76										
				2033	3854	65										
				1850	3508	58										
	215/75 R 16C	113/111R	AGILIS AGILIS ALPIN	2300	4360	69	225	740	2206	728	332	248	5.5	6.0	7.0	16 J 13
				2005	3800	58										
				1801	3415	51										
		116/114R	AGILIS AGILIS ALPIN	2500	4720	76										
				2210	4172	65										
				2011	3797	58										
	225/75 R 16C	118/116R	AGILIS AGILIS X-ICE NORTH	2640	5000	76	232	758	2254	744	338	262	6.0	6.5	7.0	16 J 13
				2334	4420	65										
				2124	4022	58										
	195/65 R 16C	100/98T	AGILIS 51 AGILIS 51 SNOW-ICE	1600	3000	54	209	670	2000	660	305	231	5.5	6.0	6.0	T/L ONLY
				1338	2510	44										
				1157	2169	36										
		104/102R	AGILIS AGILIS ALPIN	1800	3400	69										
				1569	2963	58										
				1410	2663	51										
	205/65 R 16C	103/101T	AGILIS 51 AGILIS 51 SNOW-ICE	1750	3300	54	217	682	2036	672	309	240	5.5	6.0	6.5	T/L ONLY
				1464	2760	44										
				1265	2386	36										
		107/105R	AGILIS AGILIS ALPIN	1950	3700	69										
				1700	3225	58										
				1527	2898	51										
	215/65 R 16C	106/104T	AGILIS 51	1900	3600	54	230	698	2079	686	315	254	6.0	6.5	7.0	T/L ONLY
				1589	3011	44										
				1374	2603	36										
		109/107T	AGILIS AGILIS ALPIN	2060	3900	69										
				1795	3399	58										
				1613	3055	51										
	225/65 R 16C	112/110R	AGILIS AGILIS ALPIN	2240	4240	69	237	710	2115	698	320	262	6.0	6.5	7.0	T/L ONLY
				1952	3695	58										
				1754	3321	51										
	235/65 R 16C	115/113R	AGILIS AGILIS ALPIN	2430	4600	69	250	724	2157	712	325	276	6.5	7.0	7.5	T/L ONLY
				2118	4009	58										
				1903	3603	51										
	195/60 R 16C	99/97H 99/97T	AGILIS 51 AGILIS ALPIN	1550	2920	54	209	650	1939	640	297	231	5.5	6.0	6.5	T/L ONLY
				1297	2443	44										
				1121	2111	36										
	215/60 R 16C	103/101T	AGILIS 51 AGILIS 51 SNOW-ICE	1750	3300	54	230	674	2012	664	306	254	6.0	6.5	7.0	T/L ONLY
				1641	3095	44										
				1419	2675	36										
	225/60 R 16C	105/103T	AGILIS 51	1850	3500	54	237	686	2048	676	311	268	6.5	7.0	7.5	T/L ONLY
				1548	2928	44										
				1338	2530	36										



Dimensional data

MICHELIN Agilis Camping

Rim Dia.	Size	Load Index & Speed Symbol	Range	Max Axle Loads						Dimensional Details	Rim Width (inches)			Inner tube	
				Front axle		Rear axle Single*		Rear axle Twinned*			Min.	Measuring	Max.		
				Load kg	Pressure psi	Load kg	Pressure psi	Load kg	Pressure psi						
15"	215/70 R 15CP	109/107Q	AGILIS CAMPING	2060	65	2060	80	3900	69	Dimensional Details as per Michelin Agilis see page xx	5.5	6.5	7.0	T/L ONLY	
				1875	58										
				1685	51										
	225/70 R 15CP	112/110Q	AGILIS CAMPING	2240	65	2240	80	4240	69		6.0	6.5	7.0		
				2039	58										
				1832	51										
16"	195/75 R 16CP	107/105Q	AGILIS CAMPING	1950	69	1950	80	3700	69		5.0	5.5	6.0		Use Metal Valves
				1700	58										
				1527	51										
	215/75 R 16CP	113/111Q	AGILIS CAMPING	2300	69	2300	80	4360	69		5.5	6.0	7.0		
				2005	58										
				1801	51										
	225/75 R 16CP	116/114Q	AGILIS CAMPING	2500	69	2500	80	4720	69		6.0	6.5	7.0		
				2316	58										
				2129	51										
	225/65 R 16CP	112/110Q	AGILIS CAMPING	2240	69	2240	80	4240	69		6.0	6.5	7.0		
				1952	58										
				1754	51										

*On motorhomes fitted with MICHELIN Agilis Camping, use the following rear tyre inflation pressures:

80 psi (5.5 bar) for all loads in single fitment

69 psi (4.75 bar) for all loads in twinned (dual) fitment

For advice on the optimum front tyre pressures contact Michelin with the vehicle's maximum in service axle loads or contact the vehicle manufacturer.

The front tyre inflation pressures quoted above are the minimum pressures for the load stated.

Metal clamp-in valves are recommended when using MICHELIN Agilis Camping.