

Size	Tyre		Rim ⁷⁾ (meas- uring rim bold)	TL valve (tube and valve)*)	Tyre dimensions				new		Radius stat. + / - 2 % (mm)	Rolling circum- ference + 1.5 % - 2.5 % (mm)		PR	Load Index LI	Wheel position ⁹⁾	Load capacity (kg) per axle at a tyre pressure (bar)																Speed Symbol and reference speed (km/h)					
	PR	Service description ⁶⁾			Max. standard value in operation ⁸⁾				Width	Outer- Ø							+ 1.5 % - 2.5 % (mm)	+ 1.5 % - 2.5 % (mm)		3.0	3.25	3.5	3.75	4.0	4.25	4.5	4.75	5.0	5.25	5.5	5.75	6.0						
					Stand- ard	Spe- cial	Stand- ard	Spe- cial																														
16 inch																																						
225/75 R 16 C	8	116/114 R	6 J 6 ½ J 7 J	TR 600 XHP,	232 237 242	758	764	223 228 233	744	338	2254		8	116	S	1730	1845	1960	2070	2180	2285	2395	2500							N 140 R 170 (R 170) (P 150) (L 120)								
		116/114 R (118/116 P)		114										T	3270	3485	3695	3905	4115	4320	4520	4720																
		118/116 R		118										S	1685	1800	1910	2015	2125	2230	2335	2435	2540	2640														
	10	121/120 N (118 R)		10									118	S	1685	1800	1910	2015	2125	2230	2335	2435	2540	2640														
		121/120 R											116	T	3195	3410	3615	3820	4020	4220	4420	4615	4810	5000														
		121/120 R (122 L)											121	S	1725	1835	1950	2060	2170	2275	2385	2490	2595	2695	2800	2900												
													120	T	3330	3550	3765	3980	4190	4395	4605	4805	5010	5205	5405	5600												
													118	S	1685	1800	1910	2015	2125	2230	2335	2435	2540	2640														
		122		S									1725	1835	1950	2060	2170	2275	2385	2490	2595	2695	2800	2900	3000													
	225/75 R 16 CP	8		116 R									TR 600 XHP, TR 602 HP, 40 MS		720	726	211 216 221 226	708	324	2145		6	116	FA S	1730	1845	1960	2070	2180	2285	2395	2500						
118 R		116		RA S																			1540	1640	1740	1840	1940	2035	2130	2225	2315	2410	2500					
		1.85x116		RA T																			3200	3415	3625	3830	4030	4230	4430	4625								
													10	118	FA S	1685	1800	1910	2015	2125	2230	2335	2435	2540	2640													
														1.85x116	RA S	1515	1615	1715	1815	1910	2005	2095	2190	2280	2370	2460	2550	2640										
215/70 R 16 C	6	108/106 S	5 ½ J 6 J 6 ½ J 7 J	43 GS 11.5	220 225 230 235	720	726	211 216 221 226	708	324	2145		6	108	S	1675	1785	1895	2000												S 180 T 190							
		108/106 T												106	T	3180	3390	3595	3800																			
195/65 R 16 C	6	100/98 T	5 ½ J 6 J	TR 600 XHP, TR 602 HP	204 209	670	676	196 201	660	305	2000		6	100	S	1340	1425	1515	1600											R 170 T 190								
	8	98												T	2510	2675	2840	3000																				
	8	104											S	1245	1330	1410	1490	1570	1645	1725	1800																	
		102											T	2355	2510	2665	2815	2965	3110	3255	3400																	
		100											S	1340	1425	1515	1600																					
205/65 R 16 C	6	103/101 T (99 H)	5 ½ J 6 J 6 ½ J	43 GS 11.5	212 217 222	682	686	204 209 214	672	310	2036		6	103	S	1465	1560	1655	1750											R 170 T 190 H 210								
		101												T	2760	2940	3120	3300																				
		99												S	1455	1550																						
	8	107/105 R											8	107	S	1350	1440	1525	1615	1700	1785	1865	1950															
		107/105 R (103 R)												105	T	2560	2730	2900	3060	3225	3385	3545	3700															
		107/105 R (103 T)												103	S	1465	1560	1655	1750																			
		107/105 T																																				
		107/105 T (103 T)																																				
		107/105 T (103 H)																																				